

LIABILITY



WARNING!!! The installer is responsible for any leaks resulting from installation of tubing or related fittings. **THE INSTALLER MUST CHECK OVER THE ENTIRE SYSTEM COMPLETELY WHILE UNDER PRESSURE TO ENSURE SYSTEM IS NOT LEAKING AND FUNCTIONING PROPERLY.** Liability resulting from failure to check for leaks under pressure is the sole responsibility of the installer.



Limited Two Year Warranty

1. Warranty Covers

The Reverse Osmosis Water Purification System is warranted to the original owner to be free of defects in material and workmanship from the date of manufacture for two years as follows:

- 1) The manufacturer will replace the defective parts (excluding the replaceable filters) within two years at no charge.
- 2) The replaceable filters are warranted for defects in material and workmanship only. Service life of replaceable filter varies with local water and is thus not warranted. It is recommended to replace the reverse osmosis system every ten (10) years.

2. Warranty Does Not Cover

- 1) System must be maintained and serviced with manufacturer approved replacement parts. The performance and function of the RO system is directly related to the quality of the water being treated and the particular application in which it is used. Therefore, the manufacturer liability is limited to the cost of repair or replacement of any defective part and does not include incidental or consequential damages of any kind. This warranty gives you special legal rights and you may also have other rights which vary from state to state.
- 2) Systems must be installed and operated in accordance with manufacturer recommended procedures and guidelines.

3. Reverse Osmosis System warranty conditions

- 1) Warranty is void if product failure or damage result from freezing, neglect, misapplication, fouling with sediment or scale or failure to operate the system in accordance with the instructions contained in the owner's manual.
- 2) The following operating conditions must also be followed for this warranty to be valid.
- 3) Warranty void if system is not installed by a licensed contractor.

Operating pressure: 50-80 PSI

Operating temperature: 40-100 ° F

Hardness: <120 ppm (7gpg)

TDS: <1000 ppm

pH Range: 3-11

Iron: <0.3 ppm

4. Limitations and exclusions

The manufacturer will not be responsible for any implied warranties including those of merchant ability and fitness for a particular purpose. The manufacturer will not be responsible for any incidental or consequential damages including travel expense, telephone charges, loss of revenue, loss of time, inconvenience, loss of use of the equipment and damage caused by the equipment and its failure to function properly. If a HALO Reverse Osmosis system was purchased from a 3rd party, liquidator or by any means other than an authorized licensed wholesale distributor, the warranty is void. This warranty sets forth all of manufacturer's responsibilities regarding this equipment. Failure to provide a current well water report to HALO Water Systems for analysis and recommendation voids all warranties.