

# ULTRA<sup>+</sup> PLUS

## Reverse Osmosis Purification System With Alkalinity Booster

Addresses specific contaminants in your municipal or well water for the reduction of: PFAS, PFOS, arsenic, barium, cadmium, copper, fluoride, chromium (hexavalent), lead, radium 226/228, selenium, trivalent chromium, turbidity and TDS and much more.

### Features

- Smart Faucet *Tells you when to change filters!*
- No tools required for filter change
- 1 GAL purified to 1 GAL wasted!
- Air hammer arrestor  
Extends the life of equipment  
& protects the home and family
- HALO leak detector, shuts off water
- Can be connected to an ice maker



**Smart Faucet**  
Blue light turns red  
when it's time to  
change the filters!

### TOTAL CARE

#### 5-stage quality with only 4 filters to replace!

- **System Dimensions:** 3.75" w x 4.75" d x 12.75" h
- **System Weight:** 6.1 lbs.
- **Tank Dimensions:** 11.3" d x 16.75" h
- **Tank Capacity:** 1.9-3.2 gal.  
(Depending on water pressure)
- **Tank Weight:** Full - 40 lbs.  
(Depending on water pressure)

**Stage 1:** Sediment Filter - .5 microns

**Stage 2:** Carbon block pre-filter - .5 micron

**Stage 3:** 50 gallon per day membrane

**Stage 4:** Alkalinity pH booster

### Water Saver

ONLY 1 GALLON WASTED  
PER 1 GALLON PURIFIED!

#### What is pH (potential of hydrogen)

pH is a measure of the acidity or basicity of liquids. A pH of 7 is considered neutral. Above 7 is considered basic or alkaline, and less than 7 is considered acidic.



Scan to learn more about  
the HALO Ultra Plus

**WARNING:** Intended for use treatment of cold water only. Do not exceed 80 psi. Intended for residential use only. Do not use with water that is microbiological unsafe or of unknown quality without adequate disinfection before or after the system. Intended for use treatment of cold water only. Do not exceed 80 psi. Intended for residential use only.

**NOTE:** The HALO filtration systems are intended for treatment of potable water provided by municipal water providers. While the HALO Filtration Systems may be effective for treatment of well water it is vital that a well water quality analysis be provided for review and recommendation in to ensure that optimum results can be realized. Failure to provide a current well water report to HALO Water Systems for analysis and recommendation voids all warranties



## Limited Two Year Warranty

### 1. Warranty Covers

The Reverse Osmosis Water Purification System is warranted to the original owner to be free of defects in material and workmanship from the date of manufacture for two years as follows:

- 1) The manufacturer will replace the defective parts (excluding the replaceable filters) within two years at no charge.
- 2) The replaceable filters are warranted for defects in material and workmanship only. Service life of replaceable filter varies with local water and is thus not warranted. It is recommended to replace the reverse osmosis system every ten (10) years.

### 2. Warranty Does Not Cover

- 1) System must be maintained and serviced with manufacturer approved replacement parts. The performance and function of the RO system is directly related to the quality of the water being treated and the particular application in which it is used. Therefore, the manufacturer liability is limited to the cost of repair or replacement of any defective part and does not include incidental or consequential damages of any kind. This warranty gives you special legal rights and you may also have other rights which vary from state to state.
- 2) Systems must be installed and operated in accordance with manufacturer recommended procedures and guidelines.

### 3. Reverse Osmosis System warranty conditions

- 1) Warranty is void if product failure or damage result from freezing, neglect, misapplication, fouling with sediment or scale or failure to operate the system in accordance with the instructions contained in the owner's manual.
- 2) The following operating conditions must also be followed for this warranty to be valid.
- 3) Warranty void if system is not installed by a licensed contractor.

**Operating pressure:** 50-80 PSI

**Operating temperature:** 40-100 ° F

**Hardness:** <120 ppm (7gpg)

**TDS:** <1000 ppm

**pH Range:** 3-11

**Iron:** <0.3 ppm

### 4. Limitations and exclusions

The manufacturer will not be responsible for any implied warranties including those of merchant ability and fitness for a particular purpose. The manufacturer will not be responsible for any incidental or consequential damages including travel expense, telephone charges, loss of revenue, loss of time, inconvenience, loss of use of the equipment and damage caused by the equipment and its failure to function properly. If a HALO Reverse Osmosis system was purchased from a 3rd party, liquidator or by any means other than an authorized licensed wholesale distributor, the warranty is void. This warranty sets forth all of manufacturer's responsibilities regarding this equipment. Failure to provide a current well water report to HALO Water Systems for analysis and recommendation voids all warranties.