CK10 Softener Whole House Softening Systems



	Model	Mineral Tank	Resin SQ FT	Brine Tank	Peak GPM
	H-CK10-150	10" x 54"	1.5	18" x 36"	14
	H-CK10-200	12" x 52"	2	18" x 36"	16
Ĺ	H-CK10-250	13" x 54"	2.5	18" x 36"	18

- A High flow media
- Full ported control valve
- Silky soft skin

- Self cleaning distributors
- Salt Efficient
- Metered regeneration to save water

The CK10 series by HALO. Simple maintenance, highly adaptable, and impressive flow rates. Ideal for most homes or light commercial applications. CK10 series systems include a high flow bypass and 1" plastic elbow plumbing connectors.

How it works:

The mineral deposits cling to the resin and the now-softened water exits the softener tank and flows throughout the house. During regeneration, regenerate water from the brine tank flows up the fill tube and into the softener tank. A rinse cycle commences and the regenerate water washes the mineral deposits off the resin beads.

WARNING: Do not use with water that is micro-biologically unsafe or of unknown quality without adequate disinfection before or after the system. Intended for treatment of cold water only. Do not exceed 80 psi. Intended for residential use only. Do not allow system to freeze. Maintain a temperature range between 40° -100°

Change your water. Change your life.